



HAZARD RATING  
4=EXTREME  
3=HIGH  
2=MODERATE  
1=SLIGHT  
0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>REACTIVITY</b>	<b>0</b>

SAFETY DATA SHEET  
VEXCON NO. PS120 AIM  
**CERTI-VEX PENSEAL 244 O/W AIM**

**SECTION I - GENERAL INFORMATION**

<b>PRODUCT IDENTIFICATION:</b> <b>CERTI-VEX PENSEAL 244 O/W AIM</b>	
<b>VOC CONTENT:</b>	<250 GRAMS/LITER OR <2.09 #/GAL
<b>CATEGORY:</b>	<b>WATERPROOFING CONCRETE/MASONRY SEALER</b>
<b>COMMON NAME:</b>	<b>SILANE WATER PROOFER</b>
<b>MANUFACTURER:</b>	<b>VEXCON CHEMICALS, INC</b>
<b>ADDRESS</b>	7240 STATE RD, PHILADELPHIA, PA 19135
<b>EMERGENCY NO:</b>	800.858.2828 (PolySat Inc)
<b>TELEPHONE NO:</b>	215.332.7709 (Vexcon)
<b>CHEMTREC NO:</b>	800.424.9300 (CCN# 23822)
<b>PREPARED:</b>	AUGUST 1997
<b>UPDATED:</b>	JULY 2019
<b>PREPARED BY:</b>	DARRY F. MANUEL , PRESIDENT

**SECTION II – HAZARD IDENTIFICATION**

**HAZARD CLASSIFICATION:**

**PHYSICAL HAZARDS**

Flammable Liquid – Category 2

**HEALTH HAZARDS**

Specific Target organ Toxicity - Single Exposure – Category 3  
Serious Eye Damage/ Eye Irritation – Category 2A

**ENVIRONMENTAL HAZARDS**

Acute Hazards to the aquatic environment – Category 3

**SINGLE WORD: DANGER**

**HAZARD STATEMENT:** Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.

**PRECAUTIONARY STATEMENTS:**

**PREVENTION** – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wear protective gloves, protective clothing, eye protection, face protection. Wash thoroughly after handling. Avoid breathing fumes, vapour, spray. Wear protective glove, eye protection, face protection.

**RESPONSE** – If Inhaled: if breathing is difficult remove to fresh air and keep comfortable for breathing. If in eyes: rinse cautiously with water for several minutes. Remove contacts lenses, if present and easy to do. Continue rinsing. If eye irritation persists Seek medical attention.



**SECTION III HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
TRIETHOXY (octyl) SILANE	2943-75-1	60-70%	ND	1993
POLYMER	68554-66-5	1-5%	NOT ESTABLISHED	N/A
ACETONE	67-64-1	20-30%	OSHA HAZARD: FLAMMABLE LIQUID OSHA PEL: 1000 ppm (TWA) ACGIH TLV: 500 ppm (TWA)	1090
BUTYL ACETATE	123-86-4	1-5%	ACGIH TLV 150ppm (TWA) OSHA PEL 150ppm (TWA)	1123
STODDARD SOLVENT	8052-41-3	5-10%	ACGIH TLV: 100 ppm, 525 mg/m3 (TWA) OSHA PEL: 500 ppm, 2900 mg/m3 (TWA) NIOSH REL: 350 mg/m3 (TWA)	1268
<b>THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:</b>				
COMPONENT	CAS NO.	MAX %		
1,3,5 TRIMETHYL BENZENE	95-63-6	10%	OSHA PEL: NE ACGIH TLV: 25ppm	2325

**SECTION IV FIRST AID MEASURES**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE**

**ROUTES OF EXPOSURE:**

<b>INHALATION:</b>	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. STODDARD SOLVENT COMPONENT, ACETONE COMPONENT.
<b>SKIN CONTACT:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. STODDARD SOLVENT COMPONENT, ACETONE COMPONENT.
<b>SKIN ABSORPTION:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. STODDARD SOLVENT COMPONENT, ACETONE COMPONENT.
<b>EYE CONTACT:</b>	THIS PRODUCT MAY BE AN EYE IRRITANT.
<b>INGESTION / INHALATION:</b>	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>EFFECTS OF OVEREXPOSURE:</b>	<b>TLV 50 ppm, STODDARD SOLVENT COMPONENT</b> ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
<b>ACUTE OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

**EMERGENCY AND FIRST AID PROCEDURES:**

<b>EYES:</b>	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
--------------	---------------------------------------------------------------------------------------

<b>SKIN:</b>	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
<b>INHALATION:</b>	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. <b>NOTE: THIS MATERIAL RELEASES METHYL ALCOHOL UPON HYDROLYSIS. METHYL ALCOHOL CAUSES OPTIC NEUROPATHY, METABOLIC ACIDOSIS AND RESPIRATORY DEPRESSION. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE HEADACHE, BLURRED VISION, CONSTRICTED VISUAL FIELDS, SHORTNESS OF BREATH, DIZZINESS AND VERTIGO. INGESTION OF METHYL ALCOHOL MAY LEAD TO BLINDNESS OR DEATH.</b>
<b>INGESTION:</b>	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

### SECTION V FIREFIGHTING MEASURES

<b>EXTINGUISHING MEDIA:</b>	FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY <b>REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS, OR WATER SPRAY.</b> WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES.
<b>GENERAL HAZARD:</b>	<b>FLAMMABLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.</b>
<b>ELECTRO-STATIC ACCUMULATION HAZARD:</b>	<b>USE PROPER GROUNDING</b>
<b>UNUSUAL FIRE AND EXPLOSION HAZARD:</b>	FLAMMABLE VAPORS MAY ACCUMULATE IN THE CONTAINER HEADSPACE ON FORMATION OF HYDROLYSIS BY-PRODUCTS. THIS PRODUCT IS EXTREMELY FLAMMABLE AND EXPLOSIVE UNDER NORMAL CONDITIONS IN THE PRESENCE OF FLAME OR SPARK SOURCE. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP.

### SECTION VI ACCIDENTAL RELEASE MEASURES

<b>AQUATIC TOXICITY (E.G. 96 HR. TLM):</b> DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).
<b>STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:</b> <b>LAND SPILL:</b> ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS. <b>WATER SPILL:</b> REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE

ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

### SECTION VII HANDLING AND STORAGE

<b>PRECAUTIONARY STATEMENTS:</b> PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.
<b>FIRE FIGHTING:</b> WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.
<b>OTHER HANDLING AND STORAGE REQUIREMENTS:</b> STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

### SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>VENTILATION REQUIREMENTS:</b> LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.
<b>RESPIRATORY (SPECIFY IN DETAIL):</b> THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.
<b>EYES:</b> CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.
<b>GLOVES:</b> THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.
<b>OTHER CLOTHING AND EQUIPMENT:</b> TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

### SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS

<b>BOILING POINT:</b> (760mmHg) <b>56°C / 134°F (acetone)</b>	<b>MELTING POINT:</b> -95°C, -139°F (acetone)
<b>VAPOR PRESSURE:</b> 184 mmHg@68°F/20°C (acetone)	<b>VAPOR DENSITY (AIR=1):</b> 2.0 (acetone)
<b>SOLUBILITY IN H2O % BY WT:</b> MISCIBLE	<b>% VOLATILES BY VOL:</b> 35-45%
<b>EVAPORATION RATE (BuAc=1):</b> FAST 7.7 (acetone)	<b>SPECIFIC GRAVITY (H2O=1)</b> 0.868
<b>pH (AS IS)</b> N/A	<b>pH (1% SOLN)</b> N/A
<b>APPEARANCE AND ODOR:</b> CLEAR LIQUID WITH PAINT SOLVENT ODOR	
<b>FLASH POINT:</b> (TEST METHOD)	<b>-17°C / 1.4°F (TCC) (acetone)</b>
<b>AUTOIGNITION TEMP:</b>	465°C / 869°F (acetone)
<b>FLAMMABLE LIMITS IN AIR, % BY VOL:</b>	<b>LOWER:</b> 2.5% <b>UPPER:</b> 12.8% (acetone)

**SECTION X STABILITY AND REACTIVITY**

<b>CONDITIONS CONTRIBUTING TO INSTABILITY:</b>	THIS PRODUCT IS STABLE.
<b>INCOMPATIBILITY:</b>	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:</b>	N/A WILL NOT OCCUR

**SECTION XI TOXICOLOGICAL INFORMATION**

**ACETONE**

<b>ORAL</b>	RAT LD50	5800 MG/KG
<b>INHALATION</b>	RAT LC50	1000 MG/KG
<b>IRRITATION EYE</b>	RABBIT	STANDARD DRAIZE, 20 MG, SEVERE
INVESTIGATED AS A RUMORIGEN, MUTAGEN, REPRODUCTIVE EFFECTOR		

**SECTION XII ECOLOGICAL INFORMATION**

**ACETONE**

<b>ENVIRONMENTAL FATE</b>	<b>SOIL</b>	WHEN RELEASED INTO THE SOIL, THIS MATERIAL IS EXPECTED TO READILY BIODEGRADE. WHEN RELEASED INTO THE SOIL, THIS MATERIAL IS EXPECTED TO LEACH INTO GROUNDWATER. WHEN RELEASED INTO SOIL, THIS MATERIAL IS EXPECTED TO QUICKLY EVAPORATE.
	<b>WATER</b>	WHEN RELEASED IN WATER THIS MATERIAL IS EXPECTED TO READILY BIODEGRADE. WHEN RELEASED INTO WATER THIS MATERIALS IS EXPECTED TO QUICKLY EVAPORATE. THIS MATERIAL HAS A LOG OCTONAL-WATER PARTITION COEFFICIENT OF LESS THAN 3.0. THIS MATERIAL IS EXPECTED TO BIOACCUMULATE.
	<b>AIR</b>	WHEN RELEASED INTO THE AIR, THIS MATERIAL MY BE MODERATELY DEGRADED BY REACTION WITH PHOTOCHEMICALLY PRODUCE HYDROXYL RADICALS. WHEN RELEASED INTO THE AIR , THIS MATERIAL MAY BE MODERATELY DEGRADED BY PHOTOLYSIS. WHEN RELEASED INTO THE AIR, THIS MATERIAL IS ECPETED TO BE READILY REMOVED FROM THE ATOMOSPHERE BY WET DEPOSITION.
<b>ENVIRONMENTAL TOXICITY</b>	THIS MATERIAL IS NOT EXPECTED TO BE TOXIC TO AQUATIC LIVE. THE LC50/96 HR. VALUES FOR FISH ARE OVER 100 MG/L	

**SECTION XIII DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

**SECTION XIV TRANSPORTATION INFORMATION**

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group	Quantity Limitation
DOT	GROUND	1866	RESIN SOLUTION	3,	II	ORMD – Max 30Kg gross wt (66lbs)
IATA	AIR	1866	RESIN SOLUTION	3,	II	Passenger Aircraft - 5L Cargo Aircraft - 60L
IMDG	OCEAN	1866	RESIN SOLUTION	3,	II	
<b>MARINE POLLUTANT:</b>		THIS PRODUCT DOES NOT CONTAIN A MATERIAL. ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B)				

**SECTION XV REGULATORY INFORMATION**

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 2943-75-1.

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675.

**THE REPORTABLE SPILL QUANTITY (RQ) OF THIS PRODUCT IS 5,000 POUNDS (ACETONE, BUTYL ACETATE).**

**SARA TITLE III:** UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES:  
**DELAYED HEALTH FIRE**

**ADDITIONAL REGULATORY CONCERNS:** (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

**CALIFORNIA:** WARNING: This product contains chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

**CERCLA / RQ: 5000 POUNDS (ACETONE, BUTYL ACETATE)**

**TSCA:** IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

**SECTION XVI OTHER INFORMATION**

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

**HMS HAZARD RATINGS:**  
THIS INFORMATION IS FOR PEOPLE TRAINED IN:  
NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA)  
HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)  
NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704)  
IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

VEXCON CERTI-VEX PENSEAL 244 O/W AIM	NPCA-HMIS	NFPA 704	KEY
<b>HEALTH</b>	<b>1</b>	<b>1</b>	4=SEVERE
<b>FLAMMABILITY</b>	<b>3</b>	<b>3</b>	3=SERIOUS
<b>REACTIVITY</b>	<b>0</b>	<b>0</b>	2=MODERATE
			1=SLIGHT
			0=MINIMAL