



367 Alumni Road  
Newington, CT 06111  
(860)665-9400

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

4= SEVERE  
3= SERIOUS  
2= MODERATE  
1= SLIGHT  
0= MINIMAL

MATERIAL SAFETY DATA SHEET  
A.H. HARRIS NO. 3020405

# Harris Super X VOC

## GENERAL INFORMATION

**PRODUCT IDENTIFICATION:** HARRIS SUPER X VOC  
**VOC CONTENT:** 445 GR/LITER OR 3.72 #/GAL.  
**CATEGORY:** FORM RELEASE  
**COMMON NAME:** FORM RELEASE  
**DOT SHIPPING NAME:** IN CONTAINERS LESS THAN 119 GALS.  
 HARRIS SUPER X VOC (NON-REGULATED)  
 IN CONTAINERS GREATER THAN 119 GALS: COMBUSTIBLE LIQUID,  
 N.O.S. (PETROLEUM DISTILLATES), 3, NA 1993, III  
**HEALTH AND SAFETY:** COMBUSTIBLE LIQUID: USE WITH ADEQUATE  
 VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: MAY BE  
 SKIN/EYE IRRITANT: USE OF SOLVENT RESISTANT GLOVES, GOGGLES  
 AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING  
 THIS PRODUCT

## SECTION I

**MANUFACTURER:** A.H. HARRIS AND SONS  
**CHEMTREC:** 1-800-424-9300  
**TELEPHONE NO:** 1-860-665-9400  
**ADDRESS:** 367 Alumni Road, Newington, CT 06111  
**PREPARED:** APRIL 1999  
**UPDATED:** DECEMBER 2000

## SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS. NO.	%	HAZARD DATA	UN#
PETROLEUM DISTILLATES (C9 & HIGHER)	68476-30-2	79.5%	TLV 500 PPM	1993
PETROLEUM HYDROCARBON OIL	64742-52-518	5.0	Mg/M3/3 HR.	
RELEASE AND WETTING AGENTS	2.5%		NON-HAZARDOUS	

## SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

**BOILING POINT,** 760 mm Hg: 340-600<sup>0</sup>F  
**SOLUBILITY IN H2O % BY WT:** INSOLUBLE  
**MELTING POINT:** N/A **SPECIFIC GRAVITY (H2O=1):** 0.87  
**VAPOR PRESSURE:** 1.6 mm Hg **VAPOR DENSITY (AIR=1):** 8.0  
 APPROX.  
**EVAPORATION RATE (BUOH=1):** (ETHER =1) GREATER THAN 600 X  
 SLOWER  
**PH (AS IS) NA PH (1% SOLN) NA**  
**APPEARANCE AND ODOR:** CLEAR GREEN COLOR LIQUID  
 W/PETROLEUM ODOR.

## SECTION IV FIRE AND EXPLOSION HAZARD

**FLASH POINT: (TEST METHOD):** 126° F MIN. PMCC  
**AUTOIGNITION TEMPERATURE:** 494° F  
**LOWER:** ND **UPPER:** ND  
**EXTINGUISHING MEDIA:** FOAM, DRY CHEMICAL, COA2, WATER FOG OR  
 SPRAY  
**SPECIAL FIRE FIGHTING PROCEDURES:** THE USE OF SELF CONTAINED  
 BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS.  
 WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA, BUT  
 HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID  
 SPREADING BURNING LIQUID WITH WATER USE FOR COOLING  
 PURPOSES.  
**UNUSUAL FIRE AND EXPLOSION HAZARD:** VAPORS MAY FORM  
 EXPOSIVE MIXTURES WITH AIR.  
**GENERAL HAZARD:** COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE  
 MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC  
 DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH  
 CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY"  
 CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND  
 CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE,  
 SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME,  
 SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION:  
 THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS  
 SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND  
 PROMPTLY RETURNED TO A DRUM RECONDITIONER ,OR PROPERLY  
 DISPOSED OF.  
**ELECTROSTATIC ACCUMULATION HAZAED:** USE PROPER GROUNDING

## SECTION V REACTIVITY DATA

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE  
**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG  
 OXIDIZING AGENTS, STRONG ACIDS OR BASES AND SELECTED AMINES.  
**HAZARDOUS DECOMPOSITION:** THERMAL DECOMPOSITIN IN THE  
 PRESENCE  
 OF AIR MAY YIELD CARBON MONOXIDE AND UNIDENTIFIED ORGANICS.  
**CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION:** N/A  
 WILL NOT OCCUR.

## SECTION VI HEALTH HAZARD INFORMATION

**HEALTH HAZARD DATA HAZARRD CLASSIFICATION BASIS FOR  
 CLASSIFICATION**  
**ROUTES OF EXPOSURE:**

**INHALATION:** INHALATION OF HIGH VAPOR CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS.

**SKIN CONTACT:** THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

**SKIN ABSORPTION** \_SEE ABOVE

**EYE CONTACT:** THIS PRODUCT MAY BE AN EYE IRRITANT.

**EFFECTS OF OVEREXPOSURE**

**ACUTE OVEREXPOSURE:** ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

**EMERGENCY AND FIRST AID PROCEDURES:**

**EYES:** FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES CONSULT A PHYSICIAN.

**SKIN:** IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING, SEEK PROMPT MEDICAL ATTENTION.

**SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE**

**AQUATIC TOXICITY (E.G. 96 HR. TLM):**

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND.

DISPOSE OF IN COMPLIANCE WITH EPA, STATE, AND LOCAL REGULATIONS.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS.

**SECTION VIII CONTROL MEASURES**

**VENTILATION REQUIREMENTS:**

LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY(SPECIFY IN DETAIL):** CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYES:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION, OR INJURY.

**GLOVES:** IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT:** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE

RECOMMENDED. IMPERVIOUS APRONS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS ARE RECOMMENDED.

**SECTION IX SPECIAL PRECAUTIONS**

**PRECAUTIONARY STATEMENTS:**

PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**OTHER HANDLING AND STORAGE REQUIREMENTS:**

STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

**HMIS HAZARD RATINGS:**

	NFPA-HMIS	NFPA 704	KEY
HEALTH	2	2	4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE 1=SLIGHT 0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER).

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

**THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. A.H.HARRIS ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETION OF THE INFORMATION CONTAINED HEREIN.**