SAFETY DATA SHEET

B90T104

Section 1. Identification

| Product name | : ARMORSEAL® TREAD-PLEX Water Based Acrylic Floor Coating Ultradeep Base |
|--|--|
| Product code | : B90T104 |
| Other means of identification | : Not available. |
| Product type | : Liquid. |
| Relevant identified uses of t | he substance or mixture and uses advised against |
| Paint or paint related material. | |
| Manufacturer | : THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115 |
| Emergency telephone number of the company | : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year |
| Product Information Telephone Number | : US / Canada: (800) 524-5979 Mexico: Not Available |
| Regulatory Information Telephone Number | : US / Canada: (216) 566-2902 Mexico: Not Available |
| Transportation Emergency Telephone Number | : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year |

Section 2. Hazards identification

Ultradeep Base

B90T104

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|--|
| Classification of the substance or mixture | SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |
| GHS label elements | |
| Hazard pictograms | |
| Signal word | : Warning |
| Hazard statements | : Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. |
| Precautionary statements | |
| Prevention | : Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well- ventilated area. Avoid breathing vapor. Wash thoroughly after handling. |
| Date of issue/Date of revision | : 11/24/2022 Date of previous issue : 7/28/2022 Version : 18 1/13 |

SHW-85-NA-GHS-US

ARMORSEAL® TREAD-PLEX Water Based Acrylic Floor Coating

Section 2. Hazards identification

| Hazards not otherwise classified | : None known. |
|-------------------------------------|---|
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| | This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer. FOR INDUSTRIAL USE ONLY. |
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Storage | : Store locked up. Store in a well-ventilated place. Keep container tightly closed. |
| Response | : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|------------------|-------------|-------------|
| | ≥10 - ≤25 | 1317-65-3 🥄 |
| Propylene Glycol | ≤3 | 57-55-6 |
| Paraffin Oil | ≤0.3 | 64741-89-5 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version :18 | 2/13 |
|--------------------|--|--------------|----------------------------|-------------|-------------|--------|
| B90T104 | ARMORSEAL® TREAD-PLEX Water Base Ultradeep Base | | ised Acrylic Floor Coating | | SHW-85-NA-0 | GHS-US |

Section 4. First aid measures

| Ingestion | : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
|-----------------------------|---|
| Most important symptoms/ | effects, acute and delayed |
| Potential acute health effe | <u>cts</u> |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : May cause respiratory irritation. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : No known significant effects or critical hazards. |
| Over-exposure signs/sym | <u>ptoms</u> |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version | :18 | 3/13 |
|--------------------|------------------------------------|----------------|---------------------------|-------------|---------|-----------|------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base | -PLEX Water Ba | sed Acrylic Floor Coating | | SHW-85- | NA-GHS-US | 3 |

Section 5. Fire-fighting measures

| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |
|--|---|
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protect | <u>ive e</u> | quipment and emergency procedures |
|--------------------------------|--------------------------------------|---|
| For non-emergency personnel | Ev en Pro | action shall be taken involving any personal risk or without suitable training. acuate surrounding areas. Keep unnecessary and unprotected personnel from tering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. ovide adequate ventilation. Wear appropriate respirator when ventilation is idequate. Put on appropriate personal protective equipment. |
| For emergency responders | Se | specialized clothing is required to deal with the spillage, take note of any information in ction 8 on suitable and unsuitable materials. See also the information in "For non- nergency personnel". |
| Environmental precautions | thi str | is product contains a Significant New Use Rule (SNUR) Chemical. Do not allow s product to enter drains, sewers, wastewater treatment systems, groundwater, reams, lakes or ponds. See Environmental Data Sheet (EDS) for additional tails. |
| | an | oid dispersal of spilled material and runoff and contact with soil, waterways, drains d sewers. Inform the relevant authorities if the product has caused environmental llution (sewers, waterways, soil or air). |
| Methods and materials for co | ntainı | ment and cleaning up |
| Small spill | if v pla | op leak if without risk. Move containers from spill area. Dilute with water and mop up vater-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and ace in an appropriate waste disposal container. Dispose of via a licensed waste sposal contractor. |
| Large spill | up spi spi dia (se ab | op leak if without risk. Move containers from spill area. Approach release from wind. Prevent entry into sewers, water courses, basements or confined areas. Wash illages into an effluent treatment plant or proceed as follows. Contain and collect illage with non-combustible, absorbent material e.g. sand, earth, vermiculite or atomaceous earth and place in container for disposal according to local regulations be Section 13). Dispose of via a licensed waste disposal contractor. Contaminated sorbent material may pose the same hazard as the spilled product. Note: see ction 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Sures
 Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

| Date of issue/Date | e of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version : 18 | 4/13 |
|--------------------|------------------------------------|-----------------|----------------------------|-------------|------------------|------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base |)-PLEX Water Ba | ased Acrylic Floor Coating | | SHW-85-NA-GHS-US | |

Section 7. Handling and storage

| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
|--|---|
| Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | CAS # | Exposure limits |
|-------------------|--|--|
| Calcium Carbonate | 1317-65-3OSHA PEL (United States, 5/20 TWA: 5 mg/m³ 8 hours. Form: fraction TWA: 15 mg/m³ 8 hours. Form: NIOSH REL (United States, 10/ [calcium carbonate] TWA: 5 mg/m³ 10 hours. Form: fraction TWA: 10 mg/m³ 10 hours. Form: | |
| Propylene Glycol | 57-55-6 | OARS WEEL (United States, 1/2021). TWA: 10 mg/m ³ 8 hours. |
| Paraffin Oil | 64741-89-5 | OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist |

Occupational exposure limits (Canada)

| Ingredient name | CAS # | Exposure limits |
|-----------------|-------|-----------------|
| None. | | |
| | | |

Occupational exposure limits (Mexico)

| | CAS # | Exposure limits |
|-------|-------|-----------------|
| None. | | |

Section 8. Exposure controls/personal protection

| | - | |
|----------------------------------|----|--|
| Appropriate engineering controls | : | Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
| Environmental exposure controls | : | This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |
| Individual protection measure | es | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin protection | | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |
| | | |

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

| <u>Appearance</u> | | |
|---|---|----------------|
| Physical state | : | Liquid. |
| Color | 1 | Not available. |
| Odor | : | Not available. |
| Odor threshold | : | Not available. |
| рН | : | 9.2 |
| Melting point/freezing point | : | Not available. |
| Boiling point, initial boiling point, and boiling range | : | 100°C (212°F) |

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version | :18 | 6/13 |
|--------------------|------------------------------------|-----------------|----------------------------|-------------|---------|-----------|------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base | 9-PLEX Water Ba | ased Acrylic Floor Coating | | SHW-85- | NA-GHS-US | |

Section 9. Physical and chemical properties

| Flash point | : Closed cup: 94°C (201.2°F) [Pensky-Martens Closed Cup] |
|--|--|
| Evaporation rate | : 0.09 (butyl acetate = 1) |
| Flammability | : Not available. |
| Lower and upper explosion limit/flammability limit | : Lower: 2.6% Upper: 12.5% |
| Vapor pressure | : 2.3 kPa (17.5 mm Hg) |
| Relative vapor density | : 1 [Air = 1] |
| Relative density | : 1.22 |
| Solubility(ies) | : |
| Media | Result |
| cold water | Partially soluble |
| Partition coefficient: n- | : Not applicable. |

| octanol/water | |
|---------------------------|---|
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) |
| Molecular weight | : Not applicable. |
| Aerosol product | |

: 0.734 kJ/g

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Heat of combustion

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--------------------------|---------|------------------------|----------|
| 15 - 5 | LD50 Dermal LD50 Oral | | 20800 mg/kg 20 g/kg | - - |

Irritation/Corrosion

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version | :18 | 7/13 |
|--------------------|------------------------------------|----------------|---------------------------|-------------|---------|-----------|------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base | -PLEX Water Ba | sed Acrylic Floor Coating | | SHW-85- | NA-GHS-US | |

Section 11. Toxicological information

| | 5 | | | | |
|-------------------------|--------------------------|---------|-------|---------------------------|-------------|
| Product/ingredient name | Result | Species | Score | Exposure | Observation |
| Propylene Glycol | Eyes - Mild irritant | Rabbit | - | 100 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | Skin - Mild irritant | Human | - | mg 168 hours 500 mg | - |
| | Skin - Mild irritant | Woman | - | 96 hours 30 % | - |
| | Skin - Moderate irritant | Child | - | 96 hours 30 % C | - |
| | Skin - Moderate irritant | Human | - | 72 hours 104 mg l | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | ••• | Route of exposure | Target organs |
|-------------------|------------|----------------------|------------------------------|
| Calcium Carbonate | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Name | Result |
|--------------|--------------------------------|
| Paraffin Oil | ASPIRATION HAZARD - Category 1 |

| Information on the like routes of exposure | ly : Not available. | |
|--|--|-------------------|
| Potential acute health | effects | |
| Eye contact | : Causes serious eye irritation. | |
| Inhalation | : May cause respiratory irritation. | |
| Skin contact | : Causes skin irritation. | |
| Ingestion | : No known significant effects or critical hazards. | |
| Symptoms related to t | ne physical, chemical and toxicological characteristics | |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness | |
| Date of issue/Date of revision | : 11/24/2022 Date of previous issue : 7/28/2022 | Version : 18 8/13 |
| B90T104 ARMORSE Ultradeep E | AL® TREAD-PLEX Water Based Acrylic Floor Coating ase | SHW-85-NA-GHS-US |

Section 11. Toxicological information

| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
|-----------------------------|---|
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| Delayed and immediate eff | fects and also chronic effects from short and long term exposure |
| <u>Short term exposure</u> | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health ef | f <u>ects</u> |
| Not available. | |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

<u>Toxicity</u>

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--|--|----------------------|
| Propylene Glycol | Acute EC50 >110 ppm Fresh water Acute LC50 1020000 µg/l Fresh water | Daphnia - Daphnia magna Crustaceans - Ceriodaphnia dubia | 48 hours 48 hours |
| | Acute LC50 710000 μg/l Fresh water | Fish - Pimephales promelas | 96 hours |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Propylene Glycol | - | - | Readily |

Bioaccumulative potential

Not available.

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 | Version | :18 | 9/13 |
|--------------------|------------------------------------|----------------|---------------------------|-------------|---------|-----------|------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base | -PLEX Water Ba | sed Acrylic Floor Coating | | SHW-85- | NA-GHS-US | |

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|-----------------------|----------------------------------|---|---|---|
| Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| No. | No. | No. | No. | No. |
| - | - | - | - | - |
| | Classification Not regulated No. | ClassificationClassificationNot regulated.Not regulatedNo.No. | ClassificationClassificationNot regulated.Not regulatedNo.No. | ClassificationClassificationNot regulated.Not regulated.Not regulatedNo.No.No.No. |

issue

| Date of issue/Date | of revision | : 11/24/2022 | Date of previous issu |
|--------------------|------------------------------------|----------------|---------------------------|
| B90T104 | ARMORSEAL® TREAD Ultradeep Base | -PLEX Water Ba | sed Acrylic Floor Coating |

: 7/28/2022

Section 14. Transport information

| Special precautions for user | Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations. |
|--|---|
| Transport in bulk according : to IMO instruments | Not available. |

Proper shipping name :

: Not available.

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rules: 5-Chloro-2-methylisothiazolinone; 2-Methyl-4-isothiazolin-3-one

TSCA 5(a)2 final significant new use rules: Sodium Nitrite

List name Chemical name United States - TSCA 5(a) Sodium Nitrite 2 - Final significant new use rules

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Notes

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

International regulations

| International lists | Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined. |
|---------------------|---|
|---------------------|---|

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

| | Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue | : 7/28/2022 |
|--|--------------------|----------------|---------------------------|------------------------|-------------|
| B90T104 ARMORSEAL® TREAD Ultradeep Base | | -PLEX Water Ba | sed Acrylic Floor Coating | | |

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| | Classification Justification | | | | |
|--|--|--|--|--|--|
| | TION - Category 2Calculation methodEYE IRRITATION - Category 2ACalculation methodN TOXICITY (SINGLE EXPOSURE) (Respiratory tractCalculation method | | | | |
| History | | | | | |
| Date of printing | : 11/24/2022 | | | | |
| Date of issue/Date of revision | : 11/24/2022 | | | | |
| Date of previous issue | : 7/28/2022 | | | | |
| Version | : 18 | | | | |
| Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations | | | | | |

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 7/28/2022

| | Date of issue/Date | of revision | : 11/24/2022 | Date of previous issue |
|---|--------------------|----------------|---------------------------|------------------------|
| B90T104 ARMORSEAL® TREAD- Ultradeep Base | | -PLEX Water Ba | sed Acrylic Floor Coating | |

: 7/28/2022