



1. Identification

Product identifier	BEHR® ULTRA Exterior Semi-Gloss Paint & Primer - Deep Base		
Other means of identification			
Product code	5853		
Recommended use	Architectural Coating		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Supplier	Behr Process Corp.		
	1801 E. St. Andrew Place		
	Santa Ana, CA 92705		
Telephone	714-545-7101		
Emergency telephone	+1 760 476 3962		
	+1 866 519 4752		
Access code	335213		
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Carcinogenicity	Category 2	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Warning		
Hazard statement	Suspected of causing cancer.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If exposed or concerned: Get medical advice/attention.		
Storage	Store locked up.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

3. Composition/information on ingredients

Chemical name	CAS number	%
Kaolin	1332-58-7	1 - 5
Diphenyl ketone	119-61-9	0.1 - 1
Diuron	330-54-1	0.1 - 1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for	This product is miscible in water.
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1910.	.1000)	
Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CF Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	t Values		
Components	Туре	Value	Form
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide t	o Chemical Hazards		
Components	Туре	Value	Form
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
US. Workplace Environmer	ntal Exposure Level (WEEL) Guides		
Components	Туре	Value	
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3	
logical limit values	No biological exposure limits noted	for the ingredient(s).	
propriate engineering trols	Good general ventilation should be applicable, use process enclosures maintain airborne levels below reco established, maintain airborne level	s, local exhaust ventilation, or oth ommended exposure limits. If ex	ner engineering controls to
vidual protection measures	, such as personal protective equip	ment	
Eye/face protection	Wear safety glasses with side shiel	ds (or goggles).	
Skin protection Hand protection	Wear appropriate chemical resistan	nt gloves.	
Skin protection Other	Use of an impervious apron is reco	mmended.	
Respiratory protection	If airborne concentrations are above respiratory protection. Use a positiv uncontrolled release, exposure leve air-purifying respirators may not pro	/e-pressure air-supplied respirat els are not known, or any other o	or if there is any potential for
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.	
neral hygiene	Observe any medical surveillance r	equirements. Always observe gandling the material and before	
siderations	smoking. Routinely wash work clot		
	smoking. Routinely wash work clot		

Liquid.
Liquid.
Opaque.
Slight.
Not available.
7 - 10
Not available.

Initial boiling point and boiling range	> 99 °F (> 37.2 °C)
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.08
Solubility(ies)	
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 140 KU at 25°C
Other information	
Density	9.02 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	13 g/l (including water) (Material) 37 g/l (excluding water) (Coating)
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may	be harmful.	
Skin contact	Prolonged skin contact may cause temporary irritation.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.		
Information on toxicological effe	ects		
Acute toxicity			
Components	Species		Test Results
Diphenyl ketone (CAS 119-61-9)			
Acute			
Dermal			
LD50	Rabbit		3535 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatior	1		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Suspected of causing cancer.		
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
Diphenyl ketone (CAS 11 NTP Report on Carcinogens			
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1053)		
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful.		
12 Ecological information			

12. Ecolog	gical inf	formation
------------	-----------	-----------

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.
Mobility in soil	This product is water soluble and may disperse in soil.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Exp	ort Notification (40 CF	FR 707, Subpt. D)	
Diphenyl ketone (CA: CERCLA Hazardous Sul		0.1 % One-Time Export Notification only. 302.4)	
Ammonium hydroxide (CAS 1336-21-6) Diuron (CAS 330-54-1) SARA 304 Emergency release notification Not regulated.		Listed. Listed.	
OSHA Specifically Regu Not listed.	llated Substances (29	CFR 1910.1001-1053)	
Toxic Substances Control A	ct (TSCA)	All components are listed on or exempt from the U.S. EPA TSCA Inventory List.	
Superfund Amendments and Re SARA 302 Extremely hazard Not listed.		986 (SARA)	
SARA 311/312 Hazardous chemical	Yes		
Classified hazard categories	Carcinogenicity		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section	112 Hazardous Air Po	ollutants (HAPs) List	
	112(r) Accidental Rel	ease Prevention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
US state regulations			
US. Massachusetts RTK - Su			
Ammonium hydroxide (CAS 1336-21-6) Diuron (CAS 330-54-1) Kaolin (CAS 1332-58-7)			
US. New Jersey Worker and			
3-lodo-2-propynyl butylca Ammonium hydroxide (CA Diuron (CAS 330-54-1) Kaolin (CAS 1332-58-7)		3-6)	
US. Pennsylvania Worker ar	nd Community Right-to	o-Know Law	
Ammonium hydroxide (CA Diuron (CAS 330-54-1) Kaolin (CAS 1332-58-7) US. Rhode Island RTK			
Diuron (CAS 330-54-1) Kaolin (CAS 1332-58-7)			
16. Other information, including date of preparation or last revision			
Issue date	05-February-2020		
Revision date	10-September-2020		
Version #	02		
HMIS® ratings	Health: 0* Flammability: 0 Physical hazard: 0		

List of abbreviations	DOT: Department of Transportation (49 CFR 172.101). IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG Code: International Maritime Dangerous Goods Code. LD50: Lethal Dose, 50%. MARPOL: International Convention for the Prevention of Pollution from Ships. PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.
References	HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity
Disclaimer	Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.